

ASHLAND
SAFETY DATA SHEETSAFETY KLEEN PARTS CLEANER
SFK32030
557683Page: 1
Revision Date: 01/25/2008
Print Date: 6/6/2008
MSDS Number: R0330442
Version: 1.4**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)

Product name	SAFETY KLEEN PARTS CLEANER SFK32030
Product code	557683
Product Use Description	No data

2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance: liquid,

DANGER! FLAMMABLE LIQUID AND VAPOR. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. HARMFUL IF SWALLOWED. MAY CAUSE BLINDNESS. MAY BE HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. MAY CAUSE SKIN AND RESPIRATORY TRACT IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE DERMATITIS AND BURNS.

Potential Health Effects**Routes of exposure**

No data

Eye contact

No data

Skin contact

No data

Ingestion

No data

ASHLAND
SAFETY DATA SHEET

Page: 2

Revision Date: 01/25/2008

Print Date: 6/6/2008

MSDS Number: R0330442

Version: 1.4

SAFETY KLEEN PARTS CLEANER
SFK32030
557683**Inhalation**

No data

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), liver, kidney, central nervous system, pancreas, Heart, male reproductive system, Exposure to this material may aggravate any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias. Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: mouth and throat irritation (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, discomfort in the chest, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, muscle cramps, pain in the abdomen and lower back, respiratory depression (slowing of the breathing rate), Blurred vision, shortness of breath, cyanosis (causes blue coloring of the skin and nails from lack of oxygen), high blood sugar, narcosis (dazed or sluggish feeling), visual impairment (including blindness), respiratory failure, coma, and death

Target Organs

No data

Carcinogenicity

Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. The International Agency for Research on Cancer (IARC) has classified ethylbenzene as a possible human carcinogen.

Reproductive hazard

Methanol has caused birth defects in laboratory animals, but only when inhaled at extremely high vapor concentrations. The relevance of this finding to humans is uncertain.

3. COMPOSITION/INFORMATION ON INGREDIENTS

ASHLAND

SAFETY DATA SHEET

Page: 3

Revision Date: 01/25/2008

Print Date: 6/6/2008

MSDS Number: R0330442

Version: 1.4

SAFETY KLEEN PARTS CLEANER
SFK32030
557683

Components	CAS-No.	Concentration
DIACETONE ALCOHOL	123-42-2	>=50-<60%
METHANOL	67-56-1	>=20-<30%
XYLENE	1330-20-7	>=15-<20%
ETHYL BENZENE	100-41-4	>=1.5-<5%
CYCLOHEXANONE	108-94-1	>=1.5-<5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Notes to physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30

ASHLAND
SAFETY DATA SHEET

Page: 4

Revision Date: 01/25/2008

Print Date: 6/6/2008

MSDS Number: R0330442

Version: 1.4

SAFETY KLEEN PARTS CLEANER
SFK32030
557683

hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

Water mist, Carbon dioxide (CO2), Dry chemical

Hazardous combustion products

May form: carbon dioxide and carbon monoxide, various hydrocarbons

Precautions for fire-fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions**

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for cleaning up

Page 4 / 11

ASHLAND

SAFETY DATA SHEET

SAFETY KLEEN PARTS CLEANER
SFK32030
557683

Page: 5
Revision Date: 01/25/2008
Print Date: 6/6/2008
MSDS Number: R0330442
Version: 1.4

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

No data

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

DIACETONE ALCOHOL		123-42-2
ACGIH	time weighted average	50 ppm
NIOSH	Recommended exposure limit (REL):	50 ppm
NIOSH	Recommended exposure limit (REL):	240 mg/m3
OSHA Z1	Permissible exposure limit	50 ppm
OSHA Z1	Permissible exposure limit	240 mg/m3
METHANOL		67-56-1
ACGIH	time weighted average	200 ppm
ACGIH	Short term exposure limit	250 ppm
NIOSH	Recommended exposure limit (REL):	200 ppm
NIOSH	Recommended exposure limit (REL):	260 mg/m3
NIOSH	Short term exposure limit	250 ppm
NIOSH	Short term exposure limit	325 mg/m3
OSHA Z1	Permissible exposure limit	200 ppm
OSHA Z1	Permissible exposure limit	260 mg/m3
XYLENE		1330-20-7
ACGIH	time weighted average	100 ppm
ACGIH	Short term exposure limit	150 ppm
OSHA Z1	Permissible exposure limit	100 ppm
OSHA Z1	Permissible exposure limit	435 mg/m3
NIOSH	Recommended exposure limit (REL):	100 ppm

ASHLAND
SAFETY DATA SHEET

Page: 6

Revision Date: 01/25/2008

Print Date: 6/6/2008

MSDS Number: R0330442

Version: 1.4

SAFETY KLEEN PARTS CLEANER
 SFK32030
 557683

NIOSH	Recommended exposure limit (REL):	435 mg/m3
NIOSH	Short term exposure limit	150 ppm
NIOSH	Short term exposure limit	655 mg/m3

ETHYL BENZENE **100-41-4**

ACGIH	time weighted average	100 ppm
ACGIH	Short term exposure limit	125 ppm
NIOSH	Recommended exposure limit (REL):	100 ppm
NIOSH	Recommended exposure limit (REL):	435 mg/m3
NIOSH	Short term exposure limit	125 ppm
NIOSH	Short term exposure limit	545 mg/m3
OSHA Z1	Permissible exposure limit	100 ppm
OSHA Z1	Permissible exposure limit	435 mg/m3

CYCLOHEXANONE **108-94-1**

ACGIH	time weighted average	20 ppm
ACGIH	Short term exposure limit	50 ppm
NIOSH	Recommended exposure limit (REL):	25 ppm
NIOSH	Recommended exposure limit (REL):	100 mg/m3
OSHA Z1	Permissible exposure limit	50 ppm
OSHA Z1	Permissible exposure limit	200 mg/m3

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and body protection

ASHLAND

SAFETY DATA SHEET

Page: 7

Revision Date: 01/25/2008

Print Date: 6/6/2008

MSDS Number: R0330442

Version: 1.4

SAFETY KLEEN PARTS CLEANER
SFK32030
557683

Wear resistant gloves (consult your safety equipment supplier).
To prevent repeated or prolonged skin contact, wear impervious clothing and boots.
Other protective equipment: eyewash station, emergency shower.

Respiratory protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	No data
Odour	solvent
Boiling point/boilingrange	No data
pH	No data
Flash point	54 °F / 12 °C
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	0.8217 g/cm ³ @ 60.01 °F / 15.56 °C 6.91 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data
Partition coefficient: n-octanol/water	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

ASHLAND
SAFETY DATA SHEET

Page: 8

Revision Date: 01/25/2008

Print Date: 6/6/2008

MSDS Number: R0330442

Version: 1.4

SAFETY KLEEN PARTS CLEANER
SFK32030
557683

Avoid heat, open flame, and prolonged storage at elevated temperatures., Avoid contact with:

Incompatible products

Avoid contact with:, acetaldehyde, acids, Chlorine, strong bases, strong oxidizing agents

Hazardous decomposition products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION**Acute oral toxicity**

DIACETONE ALCOHOL	LD 50 Rat: 4,000 mg/kg
METHANOL	LD L0 Human: 300 mg/kg
XYLENE	LD 50 Rat: 4,300 mg/kg
ETHYL BENZENE	LD 50 Rat: 3,500 mg/kg
CYCLOHEXANONE	LD 50 Rat: 1,535 mg/kg

Acute inhalation toxicity

METHANOL	LC 50 Rat: 64000 ppm, 4 h
ETHYL BENZENE	LC Lo Rat: 4000 ppm, 4 h
CYCLOHEXANONE	LC 50 Rat: 8000 ppm, 4 h

Acute dermal toxicity

ASHLAND
SAFETY DATA SHEETSAFETY KLEEN PARTS CLEANER
SFK32030
557683Page: 9
Revision Date: 01/25/2008
Print Date: 6/6/2008
MSDS Number: R0330442
Version: 1.4

DIACETONE ALCOHOL	LD 50 Rabbit: 13,500 mg/kg
METHANOL	LD 50 Rabbit: 12,800 mg/kg
XYLENE	LD 50 Rabbit: > 2,000 mg/kg
ETHYL BENZENE	LD 50 Rabbit: 15,433 mg/kg
CYCLOHEXANONE	LD 50 Rabbit: 948 mg/kg

12. ECOLOGICAL INFORMATION**Aquatic toxicity****Acute and Prolonged Toxicity to Fish**

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental fate and pathways

No data

13. DISPOSAL CONSIDERATIONS**Waste disposal methods**

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION**IMDG:**

ASHLAND
SAFETY DATA SHEET

Page: 11

Revision Date: 01/25/2008

Print Date: 6/6/2008

MSDS Number: R0330442

Version: 1.4

SAFETY KLEEN PARTS CLEANER
SFK32030
557683

HMIS

NFPA

3

4

0

No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).